


LIGHT

Connected socket module



Use

The connected socket module, wiring to a power outlet, allows to remotely control appliances and check the consumption (instantaneous, daily, monthly). It is also possible to receive notifications in case of anomalous consumption.

The connected socket module is compatible with any device electric and large appliances up to 16A, 3680W max (protected against overloads).

It is equiped with a LED light lit in blue when it is on. This option can be enabled or disabled in the "Home+Control" app. It can be associated with "wireless light switches". - 1 module.

Range	
Designation	Cat. Nos.
Connected socket module.	☐YW4531C
Equipped with an LED indicator.	YG4531C
Hidden reset button used to return to factory settings.	YD4531C

Colours code:

☐ White ☐ Stone ☐ Dark

Technical characteristics

- Mechanical characteristics

Protection against impacts: IK 04 Protection against solid bodies/liquids: IP 20

- Material characteristics

Mechanism casing: PC

Halogen-free UV resistant

Self-extinguishing: $+850^{\circ}$ C/30 s for insulating parts holding live parts in place.

+ 650°C/30 s for the other insulating components.

- Electrical characteristics

Voltage: 100/240 V∼ Current: 16 A Frequency: 50/60 Hz

Power: 240 Vac - 3840 cosφ 0,8

 $Standby\ consumption:\ 1\ mA$

Zigbee technology 2.4 GHz to 2.4835 GHz
Power level: REC 70-03: < 20 dBm
Range: 200 m of unobstructed space
10 m between products

- Climate characteristics

Storage temperature: $0^{\circ}\text{C to } +45^{\circ}\text{C}$ Usage temperature: $+5^{\circ}\text{C to } +45^{\circ}\text{C}$

Connection

Terminal type: screw
Terminal capacity: 2 x 2.5 mm²
Stripping length: 7 mm
Screwdriver: 3 mm flat

Standards and approvals

Compliant with installation and manufacturing standards.

See e-catalogue.


The undersigned, BTICINO, declares that the radio-electric equipment type (YW4531C, YG4531C, YD4531C) complies with directive 2014/53/EU.

The full text of the EU declaration of conformity is available on the following website: www.bticino.it/red



Connected socket module

Overall dimensions (mm)



A	В	C	D
45,2	22,5	35,75	8.6

Cleaning

Clean the surface with a cloth.

Do not use acetone, tar-removing cleaning agents or trichloroethylene.


Caution: Always test before using special cleaning products.

The plates must not be painted.




Operation

Front view



Front view without coverkey



Legend

- 1. LED indicator: useful during installation
- 2. RESET button: used to return to factory settings