

# Product Environmental Profile

## French-Belgian standard power socket outlet Matix series






### BTICINO'S ENVIRONMENTAL COMMITMENTS

- Incorporate environmental management into our industrial sites**  
 Of all Legrand sites worldwide, over 85% are ISO 14001-certified [sites belonging to the Group for more than five years].
- Offer our customers environmentally friendly solutions**  
 Develop innovative solutions to help our customers design more energy efficient, better managed and more environmentally friendly installations.
- Involve the environment in product design and provide informations in compliance with ISO 14025**  
 Reduce the environmental impact of products over their whole life cycle.  
 Provide our customers with all relevant information (composition, consumption, end of life, etc.).



### REFERENCE PRODUCT

<b>Function</b>	Connect / Disconnect during 20 years the plug of a load consuming 16 A under a voltage of 250 V while protecting the user from direct contact with live parts.	
<b>Reference Product</b>		
	BT-500SM2A 2 modules support - screws equipped	BT-AM4802BBN 2 modules cover plate - white
		
	BT-AM5430A 2P+E 16 A 250 V a.c. socket - French/Belgian standard	

Tutte le informazioni menzionate nel presente documento (caratteristiche e dati) sono suscettibili di modifiche e non possono dunque costituire un impegno da parte nostra.



### PRODUCTS CONCERNED

The environmental data is representative of the following products:

BT-500SM2A	BT-AM4802BBN	BT-AM5430A
BT-503S/2A BT-500S/23A	BT-AM4802BAV - BCN - BCD - MSL - MGL - MTA - MIR - GOS - GCR - GOR - TBC - TRC - TGG - TBM - CBN - CAV - CVC - CAR - CAB - CRD - CVS - CBU; BT-AM4819BBN - BAV - BCN - BCD - MSL - MGL - MTA - MIR - GOS - GCR - GOR - TBC - TRC - TGG - TBM.	BT-A5430A

# Product Environmental Profile

## French-Belgian standard power socket outlet Matix series



### ■ CONSTITUENT MATERIALS

This Reference Product contains no substances prohibited by the regulations applicable at the time of its introduction to the market. It respects the restrictions on use of hazardous substances as defined in the RoHS directive 2011/65/EU.

<b>Total weight of Reference Product</b>		<b>113 g</b> (all packaging included)			
Plastics as % of weight		Metals as % of weight		Other as % of weight	
Polycarbonate	27,7 %	Copper alloys	8,1 %		
ABS	10,8 %	Steel	4,5 %		
Polyamide	0,4 %				
Polystyrene	0,4 %				
Packaging					
Polyethylene	1,5 %			Wood	23,6 %
				Paper / cardboard	23,0 %
<b>Total plastics</b>	<b>40,8 %</b>	<b>Total metals</b>	<b>12,6 %</b>	<b>Total other</b>	<b>46,6 %</b>

Estimated recycled material content: 23 % by mass.



### ■ MANUFACTURE

This Reference Product comes from sites that have received ISO14001 certification.



### ■ DISTRIBUTION

The Group's products are distributed from logistics centres located to optimize transport efficiency. The Reference Product is therefore transported over an average distance of 780 km, essentially by road, representing a marketing in Europe.

Packaging is compliant with European directive 2004/12/EC concerning packaging and packaging waste. At the packaging end of life, its recycling rate is of 94 % (as % of packaging weight).



### ■ INSTALLATION

For the installation of the product, only standard tools are needed.



### ■ USE

Under normal conditions of use, this product requires no servicing, no maintenance or additional products.

# Product Environmental Profile

## French-Belgian standard power socket outlet Matix series



### END OF LIFE

The product end-of-life factors are taken into account during the design phase. Dismantling and sorting of components or materials is made as easy as possible with a view to recycling or failing that, another form of reuse. This product falls within the scope of the WEEE directive (2012/19/EU). Therefore it must be processed through local WEEE recycling/recovery channels.

• **Extended producer responsibility:**

The sale of this product is subject to a contribution to eco-organisations in each country responsible for managing end-of-life products in the field of application of the European Waste Electronic and Electrical Equipment Directive.

• **Recyclability rate of the Reference Product:**

Calculated using the method described in technical report IEC/TR 62635, the recyclability rate of the product is estimated at 95 %. This value is based on data collected from a technological channel operating on an industrial basis. It does not pre-validate the effective use of this channel for the end of life of this product.

Separated into:

- plastic materials (excluding packaging) : 37 %
- metal materials (excluding packaging) : 13 %
- packaging (all types of materials) : 45 %



### ENVIRONMENTAL IMPACTS

The evaluation of environmental impacts examines the stages of the Reference Product life cycle: manufacturing, distribution, installation, use and end-of-life. It is representative from products marketed and used in Europe, in compliance with the local current standards.

For each phase, the following modelling elements were taken in account:

<b>Manufacture</b>	Materials and components of the product, all transport for the manufacturing, the packaging and the waste generated by the manufacturing.
<b>Distribution</b>	Transport between the last Group distribution centre and an average delivery point in the sales area.
<b>Installation</b>	The end of life of the packaging.
<b>Use</b>	<ul style="list-style-type: none"> <li>• Product category: PSR 0005-ed2-2016 03 29, § 3.8 Sockets.</li> <li>• Use scenario: Power socket: non-continuous operation for 20 years at 50% of rated load, during 50% of the time. This modelling duration does not constitute a minimum durability requirement.</li> <li>• Energy model: Electricity Mix, Europe 27 - 2008.</li> </ul>
<b>End of life</b>	The default end of life scenario maximizing the impacts.
<b>Software and database used</b>	EIME V5 and its database «CODDE-2016-11»

# Product Environmental Profile

## French-Belgian standard power socket outlet Matix series



### SELECTION OF ENVIRONMENTAL IMPACTS

	Total for Life cycle		Raw material and manufacture		Distribution		Installation		Use		End of life	
	Value	Unit	Value	%	Value	%	Value	%	Value	%	Value	%
<b>Global warming</b>	1.63E+01	kgCO <sub>2</sub> eq.	3.72E-01	2%	4.39E-03	< 1%	3.15E-03	< 1%	1.59E+01	98%	6.27E-03	< 1%
<b>Ozone depletion</b>	1.24E-06	kgCFC-11 eq.	2.07E-07	17%	8.89E-12	< 1%	1.89E-11	< 1%	1.04E-06	83%	1.43E-10	< 1%
<b>Acidification of soils and water</b>	6.76E-02	kgSO <sub>2</sub> eq.	1.07E-03	2%	1.97E-05	< 1%	1.47E-05	< 1%	6.65E-02	98%	2.42E-05	< 1%
<b>Water eutrophication</b>	5.60E-03	kg[PO <sub>4</sub> ] <sup>3-</sup> eq.	1.54E-03	28%	4.53E-06	< 1%	1.08E-05	< 1%	4.01E-03	72%	2.97E-05	< 1%
<b>Photochemical ozone formation</b>	3.76E-03	kgC <sub>2</sub> H <sub>4</sub> eq.	1.05E-04	3%	1.40E-06	< 1%	1.04E-06	< 1%	3.65E-03	97%	1.88E-06	< 1%
<b>Depletion of abiotic resources - elements</b>	1.90E-04	kgSb eq.	1.88E-04	99%	1.76E-10	< 1%	1.36E-10	< 1%	1.38E-06	< 1%	3.83E-10	< 1%
<b>Total use of primary energy</b>	3.27E+02	MJ	8.79E+00	3%	6.20E-02	< 1%	4.32E-02	< 1%	3.18E+02	97%	6.98E-02	< 1%
<b>Net use of fresh water</b>	5.78E+01	m <sup>3</sup>	4.43E-02	< 1%	3.93E-07	< 1%	8.01E-07	< 1%	5.78E+01	100%	4.95E-06	< 1%
<b>Depletion of abiotic resources - fossil fuels</b>	1.87E+02	MJ	6.23E+00	3%	6.16E-02	< 1%	4.41E-02	< 1%	1.81E+02	97%	8.84E-02	< 1%
<b>Water pollution</b>	7.77E+02	m <sup>3</sup>	1.17E+02	15%	7.21E-01	< 1%	4.92E-01	< 1%	6.57E+02	85%	7.35E-01	< 1%
<b>Air pollution</b>	7.62E+02	m <sup>3</sup>	7.47E+01	10%	1.80E-01	< 1%	2.83E-01	< 1%	6.86E+02	90%	6.86E-01	< 1%

The values of the 27 impacts defined in the PCR-ed3-EN-2015 04 02 are available in the digital database of pep-ecopassport.org website.

The environmental impacts are calculated for a configuration composed by 2P+E power socket, Support and Cover plate AM4802...

For the configurations composed by 2P+E power socket, Support and Cover plate AM4819..., the environmental impacts of each phase of the lifecycle are obtained by multiplying the impacts of the Reference Product by the following coefficients:

Configuration	Total	Manufacturing	Distribution	Installation	Use	End of life
for Cover plate AM4802..	1,0	1,0	1,0	1,0	1,0	1,0
for Cover plate AM4819..	1,0	1,1	1,1	1,0	1,0	1,2

Configuration colours changes do not cause significant environmental impacts variations.

Registration N°: LGRP-00785-V01.01-EN	Drafting rules: PEP-PCR-ed3-EN-2015 04 02 Supplemented by PSR-0005-ed2-2016 03 29
Verifier accreditation N°: VH02	Information and reference documents : <a href="http://www.pep-ecopassport.org">www.pep-ecopassport.org</a>
Date of issue: 08-2018	Validity period: 5 years
Independent verification of the declaration and data, in compliance with ISO 14025:2010 Internal <input checked="" type="checkbox"/> External <input type="checkbox"/>	
The PCR review was conducted by a panel of experts chaired by Philippe Osset (SOLINNEN)	
PEP are compliant with XP C08-100-1 : 2014 The elements of the present PEP cannot be compared with elements from another program	
Document in compliance with ISO 14025 : 2010: «Environmental labels and declarations. Type III environmental declarations»	
Environmental data in alignment with EN 15804 : 2012 + A1 : 2013	

